



MOTUL® 4000 Motion 10W-30

Gasoline or Diesel Engine Oil

"Fuel Economy" performance

TYPE OF USE

Specially designed for cars requiring SAE 10W-30 viscosity oil, low HTHS and fuel economy performances.

Suitable for all types of gasoline engines, with injection or carburettor, and catalytic converter. Suitable for all type of fuel.

These oils may be unsuitable for use in some engines. Refer to the owner manual or handbook if in doubt.

PERFORMANCE

STANDARDS ACEA **A1 / B1** API SJ / CF

The new performance **ACEA A1/B1** requires fuel economy and low emission performance for engines. MOTUL 4000 Motion 10W-30 reduces friction in the engine.

Detergent, dispersive agents and anti-oxidation additivation are particularly reinforced to resist over extended oil change required by manufacturers for the new model of cars.

Anti-deposit and anti-black sludge power very efficient which allows maintaining the engine clean.

Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval : according to manufacturers' recommendations and tune to your own use.

MOTUL 4000 Motion 10W30 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	10W-30
Density at 20°C (68°F)	ASTM D1298	0.867
Viscosity at 40°C (104°F)	ASTM D445	81.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	12.1 mm ² /s
Viscosity index	ASTM D2270	145
Pour point	ASTM D97	-27°C / -16°F
Flash point	ASTM D92	220°C / 428°F
TBN	ASTM D2896	8.8 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site : www.motul.fr

09/10