



MULTI CVTF

**Continuously Variable Transmission (CVT) Fluid
fitted with chain or belt**

Technosynthese®

TYPE OF USE

High performance Technosynthese® fluid specially engineered for Continuously Variable Transmission (CVT) gearbox type.

Suitable for use in a wide range of vehicles fitted with CVT gearboxes using either chain/pulleys or belt/pulleys design.

Especially suitable for vehicles from American car makers GM, FORD, CHRYSLER,..., Asian car makers HONDA, HYUNDAI, KIA, MITSUBISHI, NISSAN, SUBARU, TOYOTA,... or European car makers AUDI, BMW, CITROËN, MERCEDES, PEUGEOT, RENAULT, ...

Attention, not recommended for CVT unit fitting hybrid vehicles. Before use always refer to the owner manual or handbook of the vehicle.

PERFORMANCES

STANDARDS AND MANUFACTURERS SPECIFICATIONS: **Refer to chart.**

MOTUL MULTI CVTF is a high tech multi vehicles CVT fluid suitable for a wide range of CVT-equipped passenger cars, including belt-CVT and chain-CVT design.

Thanks to its exclusive and dedicated formula, MULTI CVTF :

- Allows fuel economy for cars fitted with CVT automatic gearboxes by providing optimum metal-to-metal friction.
- Provides high anti-shudder performance to avoid engine vibrations for increased comfort.
- Protects gears that are more and more numerous, compact and heavily loaded.
- Gives superior automatic transmission response through smooth shift feel and reduced shift time lag.
- Improves CVT reaction at cold temperature.
- Extends life time duration due to high shear stability at hot temperature and high oxidation resistance.
- Increases wear protection of belt, chain and pulleys.
- Anti-corrosion, anti-foam.

RECOMMENDATIONS

Can be mixed only with similar lubricants.

Oil change : according to manufacturer's recommendations and adapt according to your own use.

Not recommended for CVT unit fitting hybrid vehicles.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Color	Visual	Red
Density at 20°C (68°F)	ASTM1298	0.852
Viscosity at 40°C (104°F)	ASTM D445	34.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	7.2 mm ² /s
Viscosity Index	ASTM D2270	180
Flash Point	ASTM D92	210°C / 410°F

MULTI CVTF

OEM Group	Specification
Audi (VAG)	TL 52180, TL 52516
BMW	EZL 799, #8322 0136376
Citroën	Elfmatic CVT
Dodge	NS-2, CVTF+4, #05191184AA
Fiat	Tutela Car CVT N.G.
Ford	CVT23, CVT30, MERCON C, WSS M2C 928A
General Motors	DEX-CVT
Honda	HMMF (Honda Multi Matic Fluid), Honda CVT-F, #0826099905HE, #087009006
Hyundai	SP III, Genuine CVTF, SP-CVT 1
Infiniti	NS-2
Jeep	NS-2, CVTF+4, VTF, #05191184AA
Kia	SP III, SP-CVT 1
Lexus	TC
Mercedes Benz	MB 236.20
Mini	EZL 799, #8322 0136376
Mitsubishi	Dia Queen CVTF-J1, SP III, #MZ313973
Nissan	NS-1, NS-2, #999MP-NS200P
Peugeot	Elfmatic CVT
Renault	Elfmatic CVT
Rover	Unipart Transmatic ATF
Saturn	DEX-CVT, #22688912
Subaru	NS-2, Lineartronic CVTF
Suzuki	NS-2, TC, CVT Green 1
Toyota	TC
VW (VAG)	G 052 180, G 052 516
Products	Specification
Elf	Elfmatic CVT
Esso	EZL 799, FN1975
Mopar	CVTplus4
Shell	Green 1V

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - Fax : 33 1 48 33 28 79 - Web Site: www.motul.com