



# POWER QUAD 4T 10W-40

High performance lubricant for ATVs

100% Synthetic

## TYPE OF USE

Sporty or urban ATVs...fitted with 4 stroke engines, integrated gearbox or not, wet or dry clutch, engines meeting Euro 2 or Euro 3 emission regulation, fitted with exhaust gas after treatment systems: catalytic converters, air injection into exhaust pipe...  
ATVs used for leisure.

## PERFORMANCE

STANDARDS                      API SL  
APPROVALS                     JASO MA under N° M033MOT103

### **Protection**

100% Synthetic lubricant for improved oil film resistance at high temperatures.  
Formula reinforced with anti-wear additives and improved shear resistance for improved gear protection and life time.  
Low Phosphorus and Sulfur content for better operating conditions of catalytic converters required to meet latest emission regulation.

JASO MA approved to warranty a perfect lock up of wet clutch.  
Easy gear shifting.

## RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.  
Can be mixed with synthetic or mineral lubricants.

## PROPERTIES

Color	Visual	Red
Viscosity grade	SAE J 300	<b>10W-40</b>
Density at 20°C (68°F)	ASTM D1298	0.862
Viscosity at 40°C (104°F)	ASTM D445	91 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	13.4 mm <sup>2</sup> /s
Viscosity index	ASTM D2270	148
Pour point	ASTM D97	-36°C / -33°F
Flash point	ASTM D92	228°C / 442°F
TBN	ASTM D2896	8.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. – Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79. Web Site: [www.motul.com](http://www.motul.com)

07/12