



SnowPower 4T 0W-40

Snowmobile 4 Stroke Engine Lubricant

100% Synthetic – Ester Based

TYPE OF USE

Specially designed for high performance 4 stroke engines fitted on snowmobiles: Yamaha, Skidoo, Artic Cat, Lynx...

Strongly recommended for racing.

Suitable for leaded or unleaded gasoline, winter or regular fuel and catalytic converters.

PERFORMANCE

STANDARDS

API SJ

This 100% synthetic engine oil is formulated and developed to meet the most stringent requirements of very powerful engines:

- Faster rev raisings and maximum power output.
- Outstanding engine protection at high rpm and high temperature.
- Balanced engine operating temperature.
- Easy start in polar cold.
- Avoid starter clutch sliding.

Tested in Canada, Motul SnowPower 4T 0W-40 exceeds factory requirements for 4 stroke engines.

RECOMMENDATION

Drain interval: refer to manufacturers' recommendations and tune to your own use.

MOTUL Snowpower 4T 0W-40 can be mixed with synthetic or mineral oils.

PROPERTIES

Viscosity grade	SAE J 300	0W-40
Density at 20°C (68°F)	ASTM D1298	0.859
Viscosity at 100°C (212°F)	ASTM D445	14.6 mm ² /s
Viscosity at 40°C (104°F)	ASTM D445	81.9 mm ² /s
Viscosity index	ASTM D2270	187
Pour point	ASTM D97	-57°C / -76°F
Flash point	ASTM D92	226°C / 438°F
TBN	ASTM D2896	10.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - TEL : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site : www.motul.fr

09/10