



SAFETY DATA SHEET

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : A2 AIR FILTER OIL

Product code : 18503northamerica

1.2. Relevant identified uses of the substance or mixture and uses advised against

Air filter oil

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL.

Address : 119 BOULEVARD FELIX FAURE.93300.AUBERVILLIERS CEDEX.FRANCE.

Telephone : +33 (0)1.48.11.70.00. Fax : +33 (0)1.48.33.28.79.

Email: motul_hse@motul.fr

1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : .

Other emergency numbers

To be translated (XML)

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 1 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336

Ireland : +353 1 8092566

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

HCS compliant.

Skin irritation, Category 2 (Skin Irrit. 2).

2.2. Label elements

Mixture for aerosol application.

HCS compliant.

Hazard pictograms :



GHS02



GHS07

Signal Word :

DANGER

Hazard statements :

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

Precautionary statements - Storage :

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

No data available.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	HCS	Nota	%
CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32 BUTANE	GHS02, GHS04 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	50 <= x % < 100
CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21 PROPANE	GHS02, GHS04 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	10 <= x % < 25
EC: 927-510-4 REACH: 01-2119475515-33 HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS	GHS07, GHS08, GHS02 Dgr Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336		10 <= x % < 25
CAS: 64742-54-7 EC: 265-157-1 REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC			2.5 <= x % < 10
CAS: 64742-48-9 EC: 927-241-2 REACH: 01-2119471843-32 HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336		2.5 <= x % < 10
CAS: 75-28-5 EC: 200-857-2 REACH: 01-2119485395-27 ISOBUTANE	GHS02, GHS04 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	2.5 <= x % < 10

(Full text of H-phrases: see section 16)

Information on ingredients :

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

Remove the victim to fresh air. If the symptoms persist, call a physician.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Wash immediately and abundantly with water, including under the eyelids.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

Immediately remove all soiled clothing.
Wash immediately and abundantly with soap and water.

In the event of swallowing :

Do not give the patient anything orally.
In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
Keep the person exposed at rest. Do not force vomiting.
Seek medical attention immediately, showing the label.
If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.
Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.
Spilled product may make surfaces slippery.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.
Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections



No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

- Always wash hands after handling.
- Remove and wash contaminated clothing before re-using.
- Ensure that there is adequate ventilation, especially in confined areas.
- Remove contaminated clothing and protective equipment before entering eating areas.
- Avoid contact with eyes.
- No special precaution apart from the observance of hygiene rules

Fire prevention :

- Handle in well-ventilated areas.
- Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.
- Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.
- Do not spray on a naked flame or any incandescent material.
- Do not pierce or burn, even after use.
- Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.
- Keep packages tightly closed and away from sources of heat, sparks and naked flames.
- Do not use tools which may produce sparks. Do not smoke.
- Prevent access by unauthorised personnel.
- Take precautionary measures against static discharges by bonding and grounding equipment.
- No smoking.

Recommended equipment and procedures :

- For personal protection, see section 8.
- Observe precautions stated on label and also industrial safety regulations.
- Do not breathe in aerosols.
- Packages which have been opened must be reclosed carefully and stored in an upright position.
- Ensure good ventilation at the workplace

Prohibited equipment and procedures :

- No smoking, eating or drinking in areas where the mixture is used.
- Never open the packages under pressure.
- Do not breathe fumes, vapour, spray.

7.2. Conditions for safe storage, including any incompatibilities

- Only use hydrocarbon-resistant containers, joints and pipes.

Storage

- Keep out of reach of children.
- Keep the container tightly closed in a dry, well-ventilated place.
- Keep away from all sources of ignition - do not smoke.
- Keep well away from all sources of ignition, heat and direct sunlight.
- The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

- Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

- No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm				
74-98-6	1000 ppm				
75-28-5	1000 ppm				

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes

106-97-8		1000 ppm 2400 mg/m ³		4(1 TM 1 TM)	
74-98-6		1000 ppm 1800 mg/m ³		4(1 TM 1 TM)	
75-28-5		1000 ppm 2400 mg/m ³		4(1 TM 1 TM)	

- France (INRS - ED984 / 2019-1487) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m ³	750 ppm 1810 mg/m ³		Carc	

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.
Personnel shall wear regularly laundered overalls.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.
Use eye protectors designed to protect against liquid splashes
Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.
Gloves must be selected according to the application and duration of use at the workstation.
Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.
Type of gloves recommended :
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)
Recommended properties :
- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.
Wear suitable protective clothing.
Suitable type of protective clothing :
In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.
In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.
Work clothing worn by personnel shall be laundered regularly.
After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Viscous liquid.
	Spray.

Important health, safety and environmental information

pH :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	< 1
Water solubility :	Insoluble.
Chemical combustion heat :	>= 30 kJ/g.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness. May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances**Acute toxicity :**

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Oral route : LD50 > 5000 mg/kg
Species : Rat
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 5000 mg/kg
Species : Rabbit
OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (CAS: 64742-54-7)

Oral route : LD50 > 5000 mg/kg
Species : Rat
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 5000 mg/kg
Species : Rabbit
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Inhalation route (n/a) :	LC50 > 5 mg/l Species : Rat
HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS Oral route :	LD50 > 5840 mg/kg Species : Rat
Dermal route :	LD50 > 2920 mg/kg Species : Rat
Inhalation route (n/a) :	LC50 > 23300 mg/m3 Species : Rat OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Fish toxicity :	LC50 < 30 mg/l Species : Oncorhynchus mykiss Duration of exposure : 96 h
Crustacean toxicity :	EC50 < 46 mg/l Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 > 1000 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (CAS: 64742-54-7) Fish toxicity :	LC50 > 100 mg/l Duration of exposure : 96 h
Crustacean toxicity :	EC50 > 10000 mg/l Duration of exposure : 48 h NOEC > 10000 mg/l Species : Daphnia magna OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)
Algae toxicity :	ECr50 > 100 mg/l Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS (CAS: 64742-48-9)

Biodegradability : Rapidly degradable.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (CAS: 64742-54-7)

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (CAS: 64742-54-7)

Octanol/water partition coefficient : log K_{ow} > 6**12.4. Mobility in soil**

Not very mobile in soil.

The product is insoluble in water and will spread on the surface

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

SECTION 13 : DISPOSAL CONSIDERATIONS

The appropriate waste management of the mixture and/or its container must be determined in accordance with local regulations.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

14.1. UN number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	2	See SP63	-	See SP277	F-D, S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.
For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The following regulations have been used:

- OSHA Hazard Communication Standard 29 CFR 1910.1200

- Container information:


No data available.

- Particular provisions :

Total net weight of the aerosol (active product + gas) : 245 g

- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :

NFPA 704, Labelling: Health=2 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



- Clean Water Act : Toxic Pollutants (CWA 307A)

Unlisted.

- Clean Water Act : Hazardous Substances (CWA 311)

Unlisted.

- Clean Water Act : Hazardous Substances (CWA 304b)

Unlisted.

- Clean Water Act : Priority Pollutants (CWA Priority)

Unlisted.

- Clean Air Act : Hazardous Air Pollutants (CAA 112(b) HAP (188))

Unlisted.

- Clean Air Act : Organic Hazardous Air Pollutants National Emission Standards (CAA 112(b) HON (387))

Unlisted.

- Clean Air Act : Protection of Stratospheric Ozone (CAA 602)

Unlisted.

- SARA 110

Unlisted.

- SARA 302/304

Unlisted.

- SARA 313

Unlisted.

- California proposition 65 : Chemicals known to the state to cause cancer or reproductive toxicity

Unlisted.

- Massachusetts : Right to Know

Unlisted.

- New Jersey : Right to Know

Unlisted.

- Pennsylvania : Hazardous Substance

Unlisted.

- Rhode Island : Hazardous substance list

Unlisted.

**- TSCA (Toxic Substances Control Act) - USA**

CAS	Name
64742-54-7	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC
64742-48-9	HYDROCARBONS, C9-C10, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

HCS : Hazard Communication standard (OSHA).