

TRUCK+ 15W40

Mineral

DESCRIPTION

TRUCK+ LCV 15W-40 is a multi-Fleet Lubricant for Pickups, Minibuses, Commercial vehicles, Light and Heavy Duty engines.

APPLICATIONS

Motul TRUCK+ LCV 15W-40 is a mixed fleet diesel engine oil designed to provide excellent protection for fleets containing pickups, minibuses, LCV's and heavy duty engines from a variety of manufacturers. Suitable as single lubricant in case of fleet composed of new & old generation engines on Pickups, Minibuses, Commercial vehicles, Light and Heavy Duty engines thus allowing the stock of lubricants to be reduced.

Motul TRUCK+ LCV 15W-40 is a versatile product which can be used in trucks, buses, LCVs, off-road vehicles and equipment, and also in agricultural vehicles.

ADVANTAGES

- High protection and longevity of multi-fleet engines.
- Improved dispersant and anti-oxidation properties for better protection against soot build-up and oil filter clogging.
- Superior Anti-Wear level: bore polishing protection.
- Superior detergent level: piston cleanliness and piston groove deposits control.
- Anti-corrosion, Anti-rust, Anti-foam.
- High total base number (TBN) for extended oil drain interval.

TECHNICAL CHARACTERISTICS

CHARACTERISTICS	METHOD	TRUCK+ 15W40
Viscosity grade	SAE J 300	15W-40
Density at 20°C (68°F)	ASTM D1298	0.872
Viscosity at 40°C (104°F)	ASTM D445	104.3 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm ² /s
Viscosity Index	ASTM D2270	149.0
Pour point	ASTM D97	-39.0 °C / -38.2 °F
TBN	ASTM D2896	10.5 mg KOH/g
Flash point	ASTM D92	226.0 °C / 438.8 °F

STANDARDS / APPROVALS / PERFORMANCE LEVEL

TRUCK+ 15W40 meets the following standards:

- ACEA - E7 (Replaces E5 and E3)
- API - CI-4 / SL

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral oils.

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The safety data sheet is available on www.motul.com.

Our product contains natural additives which are likely to modify the colour of the concentrates without altering its performance. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary.