

# AFB

**Stop leak for gearbox  
and hydraulic circuits.**

VERSION 2 - JAN 2022

[WWW.MECATECH-PERFORMANCES.COM](http://WWW.MECATECH-PERFORMANCES.COM)

## DEFINITION

- ◆ Regenerates seal effectiveness
- ◆ Eliminates oil seeps and leaks on shaft seals, pump casing, steering racks, steering boxes etc.
- ◆ Conveys all their effectiveness to dry and deformed joints by restoring their elasticity, size and original efficiency
- ◆ Prevents oil spillage from gearboxes. Maintains clutches dry and efficient.
- ◆ Restores optimal operation of automatic gearboxes and hydraulic systems by eliminating internal leaks.

## HOW TO USE

- ◆ Dosage of 3 to 6%
- ◆ 1 dose of 100 ml is suitable for 1.5 to 3 liters of oil
- ◆ Shake before use, add the necessary quantity into the oil using a clean syringe
- ◆ Can be used in mechanical and automatic gearboxes, transfer boxes, differentials, power steering systems and any hydraulic circuits.

## CARACTERISTICS

- ◆ **Aspect**
  - ◆ **Color**
  - ◆ **Odor**
  - ◆ **Density at 20°C**
- amber  
specific  
**0.926**

## PACKAGING

- ◆ Packaging: dose of 100ml
- ◆ Article number: MT023



TE  
DATA