

GDA[®] evolution

Anti-friction surface treatment - Anti-Seizure

WWW.MECATECH-PERFORMANCES.COM

PROPERTIES

- Multi-Action:
 - Gasoline and Diesel engines –
 - 2 and 4 strokes engines
 - Mechanical Gearbox, Axels,
 - Power steering circuit, hydraulic circuits.
- Creates a high strength lubricating film.
- Improvement of the Extreme Pressure properties of oils.
- Operation more flexible and noiseless.
- Less wear and risk of seizure at high speed and heavy load.

HOW TO USE

- Compatible with all types of oils (mineral and synthetic oils except highly graphited oils).
- Not recommended to be used in automatic gear boxes.
- Run engine or equipment until it reaches normal operating temperature, pour the dose into the oil and let it run for 15 minutes.

PHYSICOCHEMICAL PROPERTIES

◆ Colour	Amber
◆ Odour	Strong, typical
◆ Density at 20°C	1.38

SAFETY DATA

- ◆ Consult the SDSs of the products available on our site www.mecatech-performances.com.
Professional use.

TECHNICAL DATA

PACKAGING

- ◆ Packaging: 1 Dose of 120 ml. for 4 to 6 L of engine oil or 2 to 3 L. of gearbox oil and axle oil
- ◆ Art. : MT025

Information mentioned above are only for advice and don't imply any commitment of us.

