# SILICONE FLUIDE

Version:7 Review date: 4/02/2021 RE EC/2016-918 - CLP 1272/2008

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

SILICONE FLUIDE 1. 1. Preparation name:

1. 1. 1. Contains: • Hydrocarbures, C6 isoalcanes, <5% n-hexane

1. 1. 2. Product code nr: 450012

1. 1. 3. Other means of identification: UFI: GH96-W95D-010F-TD1F

1. 2. Details of the supplier of the

safety data sheet: 6 rue Jules Guesde - ZI du Pontet F-69360 Saint Symphorien d'Ozon

France

SFI D

Phone: +33 (0)4 37 25 16 16 Fax: +33 (0)4 78 21 80 70

E-mail: contact@seld-production.com

UK - National Poisons Information Service Phone: 44 / 191 22 5131 1. 3. Emergency telephone number:

1. 4. Relevant identified uses of the substance or mixture and uses

advised against:

The use of this preparation is reserved to the professional users.

For more information, to consult the chart.

#### 2. HAZARDS IDENTIFICATION

2. 1. Classification of the substance or

mixture:

\* Flam. Aerosol 1 / GHS02 - H222 \* \* STOT SE 3 / GHS07 - H336 \*

\* Aquatic. Chronic 2 / GHS09 - H411 \*

\* Asp. Tox. 1 / GHS08 - H304 \*

2. 2. Label elements:









Danger

2. 2. 1. Symbol(s) and signal word:

2. 2. 2. Contains:

• Hydrocarbures, C6 isoalcanes, <5% n-hexane

2. 2. 3. Hazard statement: H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. H336 May cause drow siness or dizziness.

2. 2. 4. Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P271 Use only outdoors or in a well-ventilated area.

P301 IF SWALLOWED: 2. 2. 5. Response:

P310a Immediately call a POISON CENTER / doctor.

P331 Do NOT induce vomiting. P391 Collect spillage. P304 IF INHALED:

P340 Remove person to fresh air and keep comfortable for breathing.

P312a Call a POISON CENTER / doctor if you feel unw ell.

2. 2. 6. Storage: P410 Protect from sunlight.

P412 Do not expose to temperatures exceeding 50 °C / 122°F.

P405 Store locked up.

G.E. Conseils® 1 / Page

### SILICONE FLUIDE

Version:7 Review date: 4/02/2021 RE EC/2016-918 - CLP 1272/2008

P403 Store in a well-ventilated place.

P233 Keep container tightly closed.

2. 2. 7. Disposal: P501a Dispose of contents / container in accordance with local / regional / national /

international regulation

2. 3. Further information(s): EUH 066 - Repeated exposure may cause skin dryness or cracking.

2. 4. Other hazards: Frequent or prolonged contacts may defat and dry the skin, leading to discomfort and

dermatitis.

Extremely flammable.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

3. 1. Component(s) contributing to the hazard:

• Hydrocarbures, C6 isoalcanes, <5% n-hexane

- CE nr: 931-254-9

- REACH registration number : 01-2119484651-34 - Conc. (w eight %) :Conc. (% pds) : % 80 < C <= 90

- GHS (Globally Harmonized System)

\* GHS02 \* Liq. infl. 2 - H225

\* GHS07 \* STOT un. 3 - H336 \* STOT un. 3. \* GHS08 \* Tox. asp. 1 - H304 \* Irr. cut. 2 - H315

\* GHS09 \* Tox. aq. chron. 2 - H411

- Miscellaneous :

LE50 / 48h / Daphnia magna = 31.9 mg/l
DSEO-R(NOELR) / / Daphnia magna = 7.14 mg/l
DSEO-R(NOELR) / / Oncorhynchus mykiss = 4.09 mg/l
DSEO-R(NOELR) / 72h / Pseudokirchneriella subcapita = 3 mg/l

LL50 / 96h / Oncorhynchus mykiss = 18.3 mg/l<math display="inline">LD50 / Skin contact / 4h / Rabbit = >3350 mg/kg

LD50 / Oral / Rat = > 16750 mg/kg

LC50 / Inhalation (vapours) / 4h / Rat = 259354 mg/m3

• Dioxyde de carbone

- CE nr: 204-696-9 - CAS nr: 124-38-9

- Conc. (w eight %): Conc. (% pds): % 1 < C <= 5

- GHS (Globally Harmonized System)

\* GHS04 - Gaz comprimés \* Gaz ss pr. - H280

- Miscellaneous :

Exposure limit values

T.L.V.  $ppm = 5000 - T.L.V. mg/m^3 = 9000 - S.T.E.L ppm = 30000 - S.T.E.L mg/m^3 = 54000$ 

The wording of the sentences are mentioned at heading 16.

#### 4. FIRST AID MEASURES

4. 1. Description of first aid measures:

4. 1. 1. General advice: In all cases of doubt, or when symptoms persist, seek medical attention.

For symptom description, see item 11.

4. 1. 2. Inhalation: Remove to fresh air, keep the patient warm and at rest. If breathing is irregular or stopped,

administer artificial respiration. Give nothing by mouth.

If unconscious, place in the recovery position and seek medical advice.

4. 1. 3. Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

proprietary skin cleaner.

4. 1. 4. Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart, and seek medical advice.

4. 1. 5. Ingestion: Rinse mouth, drink a lot of water, do not vomit, keep quiet, and go immediately to hospital or to a

doctor.

G.E. Conseils ® Page 2 / 7

### SILICONE FLUIDE

Version: 7 Review date: 4/02/2021 RE EC/2016-918 - CLP 1272/2008

4. 2. Most important symptoms and effects, both acute and delayed:

May cause drow siness or dizziness.

4. 2. 1. Inhalation:

narcotic effects Toxicité minimale

4. 2. 2. Skin contact:

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Faiblement

toxique

4. 2. 3. Eyes contact:

Splashes in the eyes may cause irritation and reversible local damage.

4. 2. 4. Ingestion:

Alcohol ingestion increases toxic product effects.

4. 3. Indication of any immediate medical attention and special treatment

needed:

In all cases of doubt, or when symptoms persist, seek medical attention.

5. FIREFIGHTING MEASURES

5. 1. Extinguishing media:

alcohol-resistant foam, carbon dioxide (CO2), pow der, w ater spray.

5. 2. Special hazards arising from the

substance or mixture:

Be careful of explosion risk.

Decomposition products may be a hazard to health. Appropriate self-contained breathing

apparatus may be required.

Fire will produce dense black smoke.

5. 3. Advice for firefighters:

Wear a self contained breathing apparatus.

5. 4. Specific method(s):

Cool closed containers exposed to fire with water spray.

5. 5. Extinguishing media w hich must

NOT be used for safety reasons:

Do not use water jet.

6. ACCIDENTAL RELEASE MEASURES

6. 1. Personal precautions, protective

Evacuate personnel to a safe area.

equipment and emergency procedures:

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid

breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6. 2. Environmental precautions:

Prevent liquid from entering sew ers, w atercourses, underground or low  $\,$  areas.

6. 3. Methods and material for containment and cleaning up:

Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth,

vermiculite, diatomaceous earth

6. 4. Reference to other sections:

Place in a suitable container for disposal in accordance with the waste regulations (see

Section 13).

7. HANDLING AND STORAGE

7. 1. Handling:

7. 1. 1. Precautions for safe

Smoking, eating and drinking is prohibited in areas of storage and use.

handling:

Avoid contact with skin and eyes. For personal protection, see Section 8.

The Manual Handling Operations Regulations may apply to the handling of containers of this product. Refer to the guide w eight indicated on the container when carrying out assessments.

7. 1. 2. Technical condition(s):

The product should only be used in areas from which all naked lights and other sources of

ignition have been excluded.

Electrical equipment should be protected to the appropriate standard.

7. 2. Storage:

7. 2. 1. Conditions for safe storage, including any incompatibilities:

No smoking. Prevent unauthorised access.

7. 2. 2. Storage condition(s):

Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

Store at temperatures between 0°C and 50°C

G.E. Conseils ® Page 3 / 7

### SILICONE FLUIDE

Version:7 Review date: 4/02/2021 RE EC/2016-918 - CLP 1272/2008

7. 2. 3. Separation of incompatible

Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

product(s):

7. 2. 4. Packaging / tank material: made of the same material as the supply container.

7. 3. Specific end use(s): None reasonably foreseeable.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8. 1. Control parameters:

8. 1. 1. Exposure limit(s): • Dioxyde de carbone :

T.L.V. ppm =  $5000 - T.L.V. mg/m^3 = 9000 - S.T.E.L ppm = 30000 - S.T.E.L mg/m^3 = 54000$ 

8. 2. Exposure controls:

8. 2. 1. Appropriate engineering

controls:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use

of local exhaust ventilation and good general extraction.

If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment

should be worn.

8. 2. 2. Eye protection: Eye protection designed to protect against liquid splashes should be w orn.

8. 2. 3. Respiratory protection: In order to avoid inhalation of mist/vapour, all spraying must be done wearing adequate

respirator.

8. 2. 4. Hand protection: solvent-resistant gloves

8. 2. 5. Skin and body protection: Cotton or cotton/synthetic overalls are normally suitable.

8. 3. Environmental exposure controls: ????

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

9. 1. Information on basic physical and

chemical properties:

9. 1. 1. Physical state: aerosol: liquid
9. 1. 2. Colour: colourless
9. 1. 3. Odour: characteristic

9. 1. 4. Melting point / freezing point: No available information on preparation.

9. 1. 5. Boiling point or initial boiling initiale: 57°C finale: 63°C

point and boiling range:

9. 1. 6. Flammability: No available information on preparation.

9. 1. 7. Low er and upper explosion LIE: 0.8% LSE: 8%

9. 1. 8. Flash point: <0°C

9. 1. 9. Auto-ignition temperature: No available information on preparation.9. 1. 10. Decomposition temperature: No available information on preparation.

9. 1. 11. PH: Not applicable.

9. 1. 12. Solubility: No available information on preparation.

9. 1. 13. Water solubility: immiscible

9. 1. 14. Fat solubility: completely soluble9. 1. 15. Solvent solubility: completely miscible

9. 1. 16. Partition coefficient n- No available information on preparation.

octanol/w ater (log value):

G.E. Conseils ® Page 4 / 7

# SILICONE FLUIDE

Version:7 Review date: 4/02/2021 RE EC/2016-918 - CLP 1272/2008

9. 1. 17. Vapour pressure: No available information on preparation.

9. 1. 18. Relative vapour density: No available information on preparation.

9. 1. 19. Density and/or relative

density:

0.69 à 15°C

9. 1. 20. Particle characteristics: No available information on preparation.

9. 1. 21. Kinematic viscosity: Not determined.

9. 2. Other information:

9. 3. Other information: Chemical heat of combustion: 41.35 KJ/g

10. STABILITY AND REACTIVITY

10. 1. Reactivity: No decomposition if stored normally.

10. 2. Chemical stability: Stable under the recommended storage and handling conditions. (See Section 7).

10. 3. Possibility of hazardous

reactions:

.

10. 4. Conditions to avoid: Avoid temperature above 50°C

10. 5. Incompatible materials: Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent

the possibility of exothermic reaction.

10. 6. Hazardous decomposition

products:

Hazardous decomposition products may be released during prolonged heating like smokes,

carbon monoxide and dioxide..

11. TOXICOLOGICAL INFORMATION

11. 1. Information on hazard classes

as defined in Regulation (EC) No

1272/2008:

There is no data available on the product itself.

11. 1. 1. Inhalation:see item nr 311. 1. 2. Skin contact:see item nr 311. 1. 3. Eyes contact:see item nr 311. 1. 4. Ingestion:see item nr 3

12. ECOLOGICAL INFORMATION

12. 1. Toxicity: Ecological problems are not known or expected under normal use.

12. 2. Persistence and degradability: Readily biodegradable.

12. 3. Bioaccumulative potential: . .

12. 4. Mobility in soil: Air: The product evaporates in atmosphere.

.

12. 5. Results of PBT and vPvB No data available.

assessment:

12. 6. Endocrine disrupting properties: No available information on preparation.

12. 7. Other adverse effects: None reasonably foreseeable.

G.E. Conseils ® Page 5 / 7

### SILICONE FLUIDE

Version:7 Review date: 4/02/2021 RE EC/2016-918 - CLP 1272/2008

12. 8. General information(s): There is no data available on the product itself.

The product should not be allowed to enter drains or water courses or be deposited where it

can affect ground or surface waters.

13. DISPOSAL CONSIDERATIONS

13. 1. Waste treatment methods: Collect all waste in suitable and labelled containers and dispose according to local legislation.

13. 2. Contaminated packaging: Empty containers can be dumped according to local legislation.

13. 3. Further Information(s): Do NOT wash away into sewer.

14. TRANSPORT INFORMATION

14. 1. General information(s): Transport follow ed ADR, IMDG, IATA

14. 2. UN number or ID number: 1950

14. 2. 1. UN proper shipping name: AEROSOLS

14. 3. Land (Road / Railw ay: ADR/RID):

14. 3. 1. Transport hazard class(es): 2
14. 3. 2. ADR/RID-Labels: 2.1
14. 3. 3. Classification code: 5F
14. 3. 4. Packing instructions: P204

14. 4. Sea (IMDG):

14. 5. Air (ICAO/IATA):

14. 6. Environmental hazards: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

14. 7. Special precautions for user: Concerning personal protective equipment to use, see item 8.

14. 8. Maritime transport in bulk according to IMO instruments:

No available information on preparation.

#### 15. REGULATORY INFORMATION

15. 1. Safety, health and environmental regulations/legislation specific for the substance or mixture:

Labelling aerosol according to the directive 2008/47/CE of the commission of April 8, 2008 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any

incandescent material. Keep away from sources of ignition - No smoking. \*/-+ % by mass of

the contents are flammable.

15. 2. Chemical safety assessment: No data available.

16. OTHER INFORMATION

16. 1. Text of the phrases listed in section 3:
 H280 Contains gas under pressure; may explode if heated.
 H225 Highly flammable liquid and vapour.

H225 Highly flammable liquid and vapour. H336 May cause drowsiness or dizziness.

H304 May be fatal if sw allow ed and enters airw ays.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

16. 2. Important remarks: As the specific conditions of use of the product are outside the supplier's control,

the user is responsible for ensuring that the requirements of relevant legislation are complied

w ith.

The user is always responsible for ensuring that the requirements of relevant legislation are

complied with.

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation it provides guidance on health safety and environmental

G.E. Conseils ® Page 6 / 7

# SILICONE FLUIDE

Version:7 Review date: 4/02/2021 RE EC/2016-918 - CLP 1272/2008

aspects of the product and should not be construed as any guarantee of technical

performance or suitability for particular applications.

16. 3. Restrictions: This information relates to the specific material designated and may not be valid in combination

with other product(s).

16. 4. History:

 16. 4. 1. First edition date:
 22/02/2005

 16. 4. 2. Previous revision date:
 19/06/2018

 16. 4. 3. Review date:
 4/02/2021

16. 4. 4. Version: 7
16. 4. 5. Review chapter(s) n°: 9
16. 5. Written by: SELD

G.E. Conseils ® Page 7 / 7