

**4 Stroke engine oil for Jet Ski  
Technosynthese®**

**TYPE OF USE**

Specially designed for Jet Ski, Water Scooter, PWC – Personal Water Craft, Watercraft,... 4 Stroke marine engines, turbo-charged or supercharged. Leisure or racing use.

Compatible with catalytic converters.

Suitable for all type of Gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

**PERFORMANCES**

STANDARDS API SM / SL

PERFORMANCES JALOS MA

The reinforced synthetic Technosynthese® base stock provides very high lubricating power which reduces frictions for higher power output and ensures resistance to very high temperatures reached in modern engines.

Outstanding detergent/dispersant properties avoiding sludge and deposits in the crankcase and maintaining engine cleanliness.

Protects against humid salt fog corrosion.

Anti-oxidation, Anti-wear, Anti-foam properties.

**RECOMMENDATIONS**

Drain interval: according to manufacturers' recommendations and tune to your own use.

Can be mixed with synthetic or mineral oils.

**PROPERTIES**

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.870

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

**4 Stroke engine oil for Jet Ski  
Technosynthese®**

Viscosity at 40°C (104°F)	ASTM D445	99.8 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	14.9 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	152.0
Pour point	ASTM D97	-36.0 °C / -33.0 °F
TBN	ASTM D2896	10.2 mg KOH/g
Flash point	ASTM D92	227.0 °C / 441.0 °F