



TRH 97

Mineral Base

DESCRIPTION

TRH 97 is a lubricant for transmissions with wet brakes and hydraulic lifter systems for farming machinery.

APPLICATIONS

TRH 97 is specially formulated for Farming Machines Transmissions fitted with wet brakes and hydraulic systems.

Suitable for Gearbox / Rear axle / Hydraulic Lifter System / Wet Brakes.

Suitable for the following farming machines: JOHN DEERE, MASSEY FERGUSON, CASE SAME, INTERNATIONAL HARVESTER, NEW HOLLAND / FORD / FIAT AGRI, RENAULT, CLASS...

TRH 97 respects most of tractors manufacturers' requirements.

This product is strongly recommended in severe applications.

ADVANTAGES

- High protection of heavy loaded gear systems.
- Friction properties adapted to wet disk brakes.
- No effects on gaskets in hydraulic systems.
- Extreme Pressure, anti-oxidation, anti-corrosion, anti-wear, anti-foam properties.

TECHNICAL CHARACTERISTICS

CHARACTERISTICS	METHOD	TRH 97
Density at 20°C (68°F)	ASTM D1298	0.886
Viscosity at 40°C (104°F)	ASTM D445	68.0 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.3 mm ² /s
Viscosity Index	ASTM D2270	148.0
Pour point	ASTM D97	-36.0 °C / -33.0 °F
Flash point	ASTM D92	230.0 °C / 446.0 °F



STANDARDS / APPROVALS / PERFORMANCE LEVEL

TRH 97 meets the following standards:

- API - GL-4

TRH 97 meets or exceeds the most common specifications and OEM requirements:

- JOHN DEERE - JDM J20C
- JOHN DEERE - JDM J20D
- CASE IH - MS 1210
- NEW HOLLAND - FNHA-2-C-201.00
- FORD NEW HOLLAND - FNHA-2-C-201.00
- FORD - M2C 41 B
- FORD - M2C 134 D
- FORD - M2C 86 B
- FORD - M2C 48 B
- FORD - M2C 53 A
- MASSEY FERGUSON - MF 1110
- WHITE MOTOR - Q-1826 WHITE FARM
- WHITE - Q-1826 WHITE FARM
- CATERPILLAR - TO-2
- ALLISON TRANSMISSION - C-4

RECOMMENDATIONS

Oil drains: refer to manufacturers' recommendations and to adjust according to your own use.

IMPORTANT NOTICE

All information and rules about health, safety and the environment are mentioned on the safety data sheet. It provides information about risks, safety procedures and first aid emergency rules. It clarifies all procedures to implement in the case of an accidental spillage, and for the disposal of the product and its effects on the environment. The specifications of our products are definite only at the time of order, and are subject to our general sale and guarantee conditions. To give our customers the latest technical developments, the general characteristics of our products may vary. The safety data sheet of this product is available at www.motul.com.