

**Lubricant for Diesel engines  
Turbocharged or Naturally Aspirated engines**

**TYPE OF USE**

All engines Diesel Turbocharged or Naturally Aspirated.

All Diesel engines :

Trucks, Bulldozers, construction vehicles, power plants, buses, farm vehicles, small boat engines...

Also suitable for gasoline engines.

**PERFORMANCES**

STANDARDS API CF / SF

Outstanding anti-wear performance for longer engine lifetime.

High TBN rate allowing use of high Sulfur content Diesel fuels.

Anti-oxidant, Anti-corrosion, Anti-rust, Anti-foam.

**RECOMMENDATIONS**

Drain intervals : according to oil analysis results.

**PROPERTIES**

Viscosity grade	SAE J 300	40
Density at 20°C (68°F)	ASTM D1298	0.887
Viscosity at 40°C (104°F)	ASTM D445	141.0 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	15.9 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	118.0
Pour point	ASTM D97	-24.0 °C / -11.2 °F
Flash point	ASTM D92	224.0 °C / 435.2 °F
TBN	ASTM D2896	10.5 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com