SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : AUTO COOL EXPERT -37°C Product code : 35468

1.2. Relevant identified uses of the substance or mixture and uses advised against

Cooling liquid

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .

Email : motul_hse@motul.fr

1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : ORFILA.

Other emergency numbers

UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 1 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336 Ireland : +353 1 8092566

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Specific target organ toxicity (repeated exposure), Category 2 (STOT RE 2, H373).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



Signal Word :	
WARNING	
Product identifiers :	
EC 203-473-3	ETHYLENE GLYCOL
Hazard statements :	
H373	May cause damage to organs through prolonged or repeated exposure (kidneys) (if swallowed).
Precautionary statements -	General :
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Precautionary statements -	Response :
P314	Get medical advice/attention if you feel unwell.
Precautionary statements -	Disposal :
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.

2.3. Other hazards

The mixture contains substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

3.2. Mixtures

Identification	(EC) 1272/2008	Note	%
	. ,		
CAS: 107-21-1	GHS07, GHS08	[1]	50 <= x % < 100
EC: 203-473-3	Wng		
REACH: 01-2119456816-28	Acute Tox. 4, H302		
	STOT RE 2, H373		
ETHYLENE GLYCOL			
CAS: 532-32-1	GHS07	[1]	2.5 <= x % < 10
EC: 208-534-8	Wng		
REACH: 01-2119460683-35	Eye Irrit. 2, H319		
SODIUM BENZOATE			
INDEX: 005-011-02-9	GHS08	[1]	0 <= x % < 1 *
CAS: 12179-04-3	Dgr	[2]	
EC: 215-540-4	Repr. 1B, H360FD	[6]	
REACH: 01-2119490790-32			
DISODIUM TETRABORATE			
PENTAHYDRATE			

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

[6] Substances of very high concern (SVHC).

Other data :

*This substance has a specific concentration limit (SCL)

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Remove the victim to fresh air. If the symptoms persist, call a physician.

In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

In the event of splashes or contact with skin :

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- multipurpose ABC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Do not get in eyes, on skin, or on clothing.

Fire prevention :

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

No smoking.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid exposure - obtain special instructions before use.

Ensure good ventilation at the workplace Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used. Do not breathe fumes, vapour, spray.

7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.

Only use hydrocarbon-resistant containers, joints and pipes.

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

2

Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :		
107-21-1	52	20	104	40	Peau		
- ACGIH TI	LV (American Conferer	nce of Governmental	Industrial Hygienists,	Threshold Limit Valu	les, 2010) :		
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :		
107-21-1	-	-	100	-	-		
12179-04-3	2 (I) mg/m3	6 (I) mg/m3		A4			
- Germany	- AGW (BAuA - TRGS	900, 08/08/2019) :	1			1	
CAS	VME :	VME :	Excess	Notes			
107-21-1		10 ppm		2(I)			
		26 mg/m ³					
532-32-1		10 mg/m ³		2 (II)			
- France (II	NRS - ED984 / 2019-14	487):					
CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :	
107-21-1	20	52	40	104	*	84	
- UK / WEL	(Workplace exposure	limits, EH40/2005, 2	011) :			1	
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :		
107-21-1	20 ppm	40 ppm					
	52 mg/m ³	104 mg/m ³					
12179-04-3	1 mg/m3	_	_	_	-		

12173-0

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

SODIUM BENZOATE (CAS: 532-32-1) Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

ETHYLENE GLYCOL (CAS: 107-21-1)

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL : Workers. Dermal contact.

Dermal contact. Long term systemic effects. 62.5 mg/kg body weight/day

Inhalation. Long term systemic effects. 3 mg of substance/m3

Inhalation. Long term local effects. 0.1 mg of substance/m3

Consumers.

Ingestion. Long term systemic effects. 16.6 mg/kg body weight/day

Dermal contact. Long term systemic effects. 31.25 mg/kg body weight/day

Inhalation. Long term systemic effects. 1.5 mg of substance/m3

Inhalation. Long term local effects. 0.06 mg of substance/m3

Workers. Dermal contact. Long term systemic effects. 106 mg/kg body weight/day

Inhalation. Long term systemic effects. 35 mg of substance/m3

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) AUTO COOL EXPERT -37°C - 35468

Final use:

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Predicted no effect concentration (PNEC):

SODIUM BENZOATE (CAS: 532-32-1) Environmental compartment: PNEC :

ETHYLENE GLYCOL (CAS: 107-21-1) Environmental compartment: PNEC :

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction. Personnel shall wear regularly laundered overalls.

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :

Consumers.

Dermal contact. Long term systemic effects. 53 mg/kg body weight/day

Inhalation. Long term systemic effects. 7 mg of substance/m3

Soil. 0.276 mg/kg

Fresh water. 0.13 mg/l

Sea water. 0.013 mg/l

Intermittent waste water. 305 µg/l

Fresh water sediment. 1.76 mg/kg

Marine sediment. 0.176 mg/kg

Waste water treatment plant. 10 mg/l

Soil. 1.53 mg/kg

Fresh water. 10 mg/l

Sea water. 1 mg/l

Intermittent waste water. 10 mg/l

Fresh water sediment. 37 mg/kg

Marine sediment. 3.7 mg/kg

Waste water treatment plant. 199.5 mg/l



Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas. - Eye / face protection

- Lye / lace protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVC (polyvinyl chloride)

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Dhunda al atata k	
Physical state :	Fluid liquid.
Color:	green
Important health, safety and environmental in	formation
pH :	8.60 .
	Slightly basic.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	1.0694
Water solubility :	Soluble.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause severe damage to organs in the event of repeated or prolonged exposure.

11.1.1. Substances

Dermal route :

Acute toxicity :

ETHYLENE GLYCOL (CAS: 107-21-1) Oral route :

LD50 = 1600 mg/kg Species : Cat

LD50 > 3500 mg/kg

Inhalation route (Vapours)):

Species : Rat LC50 2.5

Species : Rat

Specific target organ systemic toxicity - repeated exposure :

ETHYLENE GLYCOL (CAS: 107-21-1)	
Oral route :	150 < C <= 300 mg/kg body weight/day
	Duration of exposure : 28 jours

11.1.2. Mixture

Skin corrosion/skin irritation :

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

Serious damage to eyes/eye irritation :

Mild eye irritation

Aspiration hazard :

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

ETHYLENE GLYCOL (CAS: 107-21-1)		
Fish toxicity :	LC50 = 18000 mg/l	
	Species : Oncorhynchus mykiss	
	Duration of exposure : 96 h	

EC50 = 100 mg/l Species : Daphnia magna Duration of exposure : 48 h

ECr50 < 13000 mg/l Species : Selenastrum capricornutum Duration of exposure : 96 h

12.1.2. Mixtures

Algae toxicity :

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

Crustacean toxicity :

12.2.1. Substances

ETHYLENE GLYCOL (CAS: 107-21-1) Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

German regulations concerning the classification of hazards for water (WGK, VwVwS vom 27/07/2005, KBws) :

WGK 1 : Slightly hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

- 14.1. UN number
- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- -
- 14.4. Packing group
- 14.5. Environmental hazards
- -
- 14.6. Special precautions for user

-

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

- The following regulations have been used:
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)
- Container information:

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, VwVwS vom 27/07/2005, KBws) : WGK 1 : Slightly hazardous for water.
- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) : NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

<u> </u>			
	H302	Harmful if swallowed.	
	H319	Causes serious eye irritation.	
	H360FD	May damage fertility. May damage the unborn child.	
	H373	May cause damage to organs through prolonged or repeated exposure .	

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.