

MOTUL**AUTO COOL CLASSIC -25°C**

Ready to use cooling liquid. Anti-corrosion & antifreeze, protection -25°C / -13°F
Nitrite free / Amine free / Phosphate free

TYPE OF USE

MOTUL AUTO COOL CLASSIC -25°C is a ready to use cooling liquid, four seasons, based on monoethyleneglycol, using non-organic additives.

Recommended for all cooling systems: passenger cars, heavy duty, construction and agriculture vehicles, gardening, ships, stationary engines ...

PERFORMANCES

STANDARDS AFNOR NF R 15-601
 BRITISH STANDARD BS 6580
 SAE J1034

Contains a bitterness agent to prevent from drinking: coolants and antifreezes have a sweet taste but are harmful.

Protects the cooling system from freezing and metallic parts from corrosion.

Provides an excellent thermal exchange and increase engine cooling efficiency. Seals, rubber pipes and plastic parts friendly.

RECOMMENDATIONS

Ready to use, do not add any water.

Drain intervals: Refer to the manufacturers' recommendation.

Do not mix with organic products.

This product should not be used to protect drinking water systems against freezing.

Attention, control or drain the coolant only when the engine is cold.

Dangerous. Respect the use and handling recommendations.

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

motul.com



AUTO COOL CLASSIC -25°C



Ready to use cooling liquid. Anti-corrosion & antifreeze, protection -25°C / -13°F
Nitrite free / Amine free / Phosphate free

PROPERTIES

Color	Visual	Green
Density at 20°C (68°F)	ASTM D4052	1.056
Pour point	ASTM D97	-27.0 °C / -17.0 °F
pH	ASTM D1287	8.1
Initial crystallization	ASTM D1177	-23.0 °C / -9.0 °F
Freezing point		-25.0 °C / -13.0 °F
Alkalinity reserve	ASTM D1121	4.7 mg KOH/g
Boiling point		106.0 °C / 223.0 °F